


"Walk- and Driveway" with Stabilodrain® SD 30

Detail:
Edging between Hard Landscape and Vegetation



System build-up

- 1.1 Paving, e.g. concrete pavers
Depth: ≥ 100 mm for cars up to 3 t
 ≥ 120 mm for lorries up to 16 t
 ≥ 140 mm for lorries exceeding 16 t
- 1.2 Bedding layer, stone chippings, poor in lime, 30-50 mm
- 1.3 Compacted base layer, e.g. gravel, poor in lime
Depth: ≥ 150 mm for cars up to 3 t
 ≥ 200 mm for lorries up to 16 t
 ≥ 250 mm for lorries exceeding 16 t
- 1.4 Filter Sheet PV
- 1.5 Stabilodrain® SD 30, filled with stone chippings (see 1.2)
- 1.6 Filter Sheet PV
- 1.7 Roof construction with suitable waterproofing

Note:

The detailed solution shown here refers mainly to the ZinCo System Build-up. The roof construction itself as well as any other constructions are shown schematically and must be planned according to the relevant standards and guidelines.

Project:

-

Version: 28.11.2018 PBi/ EVo **Reviewed:** - **Scale:** none **Size:** A 4

Abgr01_G+F_SD30_Fd0.dwg

- 2.1 Edging, e.g. concrete kerb in reinforced concrete foundation
- 3.1 Lawn, perennials, and with sufficient substrate depth also shrubs and small trees
- 3.2 System Substrate "Roof Garden" or System Substrate "Lawn", ≥ 200 mm.
For total substrate depth exceeding 350-400 mm:
in project specific combination with mineral sub-substrate 'Zincolit Plus'
- 3.3 Filter Sheet TG
- 3.4 Stabilodrain® SD 30

Authorized by ZinCo GmbH, Lise-Meitner-Str. 2,
72622 Nuertingen/ Germany; Tel: + +49/7022-6003-0
info@zinco-greenroof.com; www.zinco-greenroof.com

Subject to technical alterations and printing errors.

