



- 2.1 Clamping Profile AP 150
 2.2. Protection Mat Strip SM-R

"Driveway" with Protectodrain® PD 250

Detail:
 Roof Edge

System build-up

- 1.1 Paving, e.g. concrete pavers
 Depth: ≥ 100 mm for cars up to 3 t
 ≥ 120 mm for lorries up to 16 t
 ≥ 140 mm for lorries exceeding 16 t
- 1.2 Bedding layer, poor in lime, 30-50 mm
- 1.3 Gravel base layer, poor in lime
 Depth: ≥ 150 mm for cars up to 3 t
 ≥ 200 mm for lorries up to 16 t
 ≥ 250 mm for lorries exceeding 16 t
- 1.4 Filter Sheet PV
- 1.5 Protectodrain® PD 250
- 1.6 Slip Sheet TGF 20 (2 layers)
- 1.7 Roof construction with root resistant waterproofing

Note:

The detailed solution shown here refers mainly to the ZinCo System Build-up. The roof construction itself as well as any other constructions are shown schematically and must be planned according to the relevant standards and guidelines.

Project:

-

Version:	Reviewed:	Scale:	Size:
26.11.2018	EV0/ JGI	-	none
			A 4

Dr01_G+F_PD250_Fd.dwg

Authorized by ZinCo GmbH, Lise-Meitner-Str. 2,
 72622 Nuertingen/ Germany; Tel: ++49/7022-6003-0
 info@zinco-greenroof.com; www.zinco-greenroof.com

Subject to technical alterations and printing errors.

