- 2.1 - 2.2 2.3

- 2.1 Inspection Chamber KS 30-E with movable collar
- 2.2 Paver as mowing edge
- 2.3 Roof outlet

"Roof Garden" with Floradrain® FD 60 neo

Detail:

Roof Outlet with Inspection Chamber

System build-up

- 1.1 Lawn, perennials, with sufficient substrate depth also shrubs and small trees
- 1.2 System Substrate "Roof Garden" or System Substrate "Lawn", ≥ 200 mm, for total substrate depth exceeding 350 mm in project specific combination with mineral sub-substrate Zincolit® Plus
- 1.3 Filter Sheet SF
- 1.4 Floradrain[®] FD 60 neo filled with ca. 27 l/m² Zincolit[®] Plus, (diffusion openings facing upwards)
- 1.5 Protection Mat ISM 50
- 1.6 Roof construction with root resistant waterproofing

Note:

The detailed solution shown here refers mainly to the ZinCo System Build-up. The roof construction itself as well as any other constructions are shown schematically and must be planned according to the relevant standards and guidelines.

Project:

-

 Version:
 Reviewed:
 Scale:
 Size:

 12.12.2018 JGI/ EVo
 none
 A 4

Entw01 Int FD60neo Fd0.dwg

Authorized by ZinCo GmbH, Lise-Meitner-Str. 2, 72622 Nuertingen/ Germany; Tel: ++49/7022-6003-0 info@zinco-greenroof.com; www.zinco-greenroof.com

ZinCo

Subject to technical alterations and printing errors.