

"Driveway" with Protectodrain[®] PD 250

Detail:

System Build-Up

System build-up

- 1.1 Paving, e.g. concrete pavers Depth: \geq 100 mm for cars up to 3 t
 - $11: \geq 100 \text{ min for cars up to 31}$
 - \geq 120 mm for lorries up to 16 t
 - ≥ 140 mm for lorries exceeding 16 t
- 1.2 Bedding layer, poor in lime, 30-50 mm
- 1.3 Gravel base layer, poor in lime
 - Depth: \geq 150 mm for cars up to 3 t
 - ≥ 200 mm for lorries up to 16 t
 - ≥ 250 mm for lorries exceeding 16 t
- 1.4 Filter Sheet PV
- 1.5 Protectodrain[®] PD 250
- 1.6 Slip Sheet TGF 20 (2 layers)
- 1.7 Roof construction with root resistant waterproofing

Note:

The detailed solution shown here refers mainly to the ZinCo System Build-up. The roof construction itself as well as any other constructions are shown schematically and must be planned according to the relevant standards and guidelines.

Project:

Version:	Reviewed :	Scale:	Size:
26.11.2018 EVo/ JGI	-	none	A 4

Sys_G+F_PD250_Fd.dwg

Authorized by ZinCo GmbH, Lise-Meitner-Str. 2, 72622 Nuertingen/ Germany; Tel: ++49/7022-6003-0 info@zinco-greenroof.com; www.zinco-greenroof.com



Subject to technical alterations and printing errors.