# Product Data Sheet Filter Sheet SF



Geotextile of thermally strengthened polypropylene, applicable as filter sheet above drainage elements for normal mechanical stress.

### **Technical Data**

### Filter Sheet SF

Thermally strengthened filter sheet of Polypropylene.

Thickness: ca. 0.60 mm
Weight: ca. 100 g/m²

Colour: grey

Penetration force according

to EN ISO 12236: ca. 1100 N

Strength class: 2

Tensile strength (200 mm) according

to EN ISO 10319: ca. 7.0 kN/m

Tensile extension lengthwise/crosswise: ca. 40% / 55%

Flow rate (H<sub>50</sub>) according

to EN ISO 11058: ca. 70  $I/(m^2 \cdot s)$  ( $\triangleq 0.07 \text{ m/s}$ )

Effective opening width (O<sub>90</sub>)

according to EN ISO 12956: ca. 95  $\mu$ m

ca. 10.00 m

Dimensions:

length:

length: ca. 100.00 m width: ca. 2.00 m Order No. 2100

width: ca. 1.00 m Order No. 2102 width: ca. 2.00 m Order No. 2101


**C** € 0799-CPD-74

## **Features**

- resistant to mechanical stress
- various application possibilities
- resistant to all naturally occurring acids and alkali
- chemically and biologically neutral
- especially high passage of water
- quick and easy installation
- non-rotting

# **Application Example**

"Extensive Green Roof Type Rockery Type Plants according to ETA-13/0668"



Plant layer "Rockery Type Plants"

System Substrate "Rockery Type Plants", ca. 80 l/m²

Filter Sheet SF Floradrain® FD 25-E Protection Mat SSM 45

Roof construction with root resistant waterproofing

# **Specification Suggestion**

Thermally strengthened sheet of polypropylene; weight ca.  $100~g/m^2$ , penetration force according to EN ISO 12236: ca. 1100~N, strength class 2, flow rate ( $H_{50}$ ) according to EN ISO 11058: ca.  $70~l/(m^2 \cdot s)$ , effective opening width ( $O_{90}$ ) according to EN ISO

12956: ca. 95  $\mu$ m, delivery and installation according to manufacturer's instructions.

Make: ZinCo Filter Sheet SF Enquiries: ZinCo GmbH, Phone: +49 7022 6003-0



€ ETA-13/0668